

**POINT LEVEL DETECTION - VIBRATING TUNING FORK  
ORDERING INFORMATION**

Code	Specifications
VTK - DC	Supply voltage 20 - 60 VDC 3 wire <PLC>
VTK - R	Supply voltage 20 - 60 VDC / 20 - 264 VAC / 1 relay SPDT 250 VAC - 5A max.
MVTK - DC	Supply voltage 20 - 60 VDC
MVTK - AC	Supply voltage 85 - 264 VAC (2 wire) - Direct Load Switching

  

Code	Process Connection
1	3/4" Thread
2	1" Thread
3	1 1/2" Tri-Clamp
4	2" Tri-Clamp
5	Flange 2" ANSI, 150lb. 316 S.S.
6	Other - Specify

  

Code	Type of thread
B	BSP
N	NPT
H	Hygienic Fitting with Coupling (See Note)
0	Not a thread

  

Code	Insertion length
S	L=3 1/8" (80mm) - Standard
L	Other - Specify

  

Code	Enclosure
N	Glass filled nylon
A	Aluminum die cast

  

Code	Electrical Connection
C	Cable gland with 1/2"NPT conduit entry
M	M12 connector
T	1/2" NPT conduit entry

  

Code	Coating
PTFE	Hallar / Tefzel
0	None
X	Other - Specify

--	--	--	--	--	--	--

**NOTE:** The hygienic fitting is available only with 1"BSP threaded connection.